TS Commercial Grade™

COLOR: White

BASIC USES:

- Protects against water, UV, weather
- Roof maintenance
- Wall coating
- Energy Savings

PRODUCT DESCRIPTION:

Elastomeric TS Commercial Grade™, with enhanced adhesive and flow agents, easily produces an attractive and effective blemish-free new weathering surface for roofs and walls that repels moisture, UV, and weather. The smooth finish helps assure improved results with any application. Special weather repelling polymers, blended with pure titanium dioxide, develop the rubber like shield that remains flexible and will not yellow over time. Achieves superior bleed-through and stain blocking too. The high resin content eliminates any need for a primer step. Applies to bituminous surfaces, metal, masonry, block, and concrete. Once cured, TS Commercial Grade™ becomes effective in all climates.

FEATURES:

- Permanently flexible
- Caulks and seals at the same time
- Excellent weather, pollution, and acid rain resistance
- Stable to moisture in as little as 4 hours
- Breathes
- Low VOC
- ENERGY STAR® Partner Product - CRRC® Certification

WET MATERIAL

Typical Product Characteristics:

Viscosity	90 – 105 K.U.
Weight per gallon	11 – 12 lb.
Solids	55 - 60%
Flashpoint of solvent	N/A
VOC	<500 g/l
pH	4 - 6
Dry to touch @ 77° F (50% rel. humidity)	4 hrs

CURED COATING

Typical Performance Properties:

Ultimate Elongation	550%
Ultimate tensile strength	1000 psi
Perm Rating	25 perms
Solar Reflectivity	86.3%
Thermal Emittance (initial/aged)	0.88
SRI (initial/aged)	109
Service Temperature	-20° - 140° F.

OMTDTSCG204028

Topps Products Inc. • P O Box 515, Stilwell, KS 66085-0515 USA
Tel. (913) 685-2500 • Fax. (913) 851-9700 • e-mail: support@toppsproducts.com