# Topps Silicone Roof Patch/ Hybrid Roof Repair Patch 10.3oz Tube

## 100% Solids Plasticizer Free Self Leveling Moisture Cure Sealant

## For Professional Use Only

### DESCRIPTION

- Industry leading plasticizer free urethane/silicone hybrid formulation
- Self-Leveling technology for all seams, fasteners, ridge caps, flashings, and penetrations.
- Moisture Curing multi-purpose one-component paintable sealant/adhesive.
- Adheres to all silicones
- Designed for Industrial uses requiring elasticity, high strength, and excellent adhesion.
- May be applied to surfaces at or below freezing temperatures. Make all attempts to remove frost.
- Performance at temperatures as low as -40 degrees F.
- Bonds to damp surfaces and can be applied in the rain.
- Cures to a Waterproof tough flexible sealant.
- Low odor and minimal shrinkage.
- Non-staining and mildew resistant.
- UV resistant.
- VOC Compliant.

### RECOMMENDED USES

Industrial uses requiring high elasticity, high strength, and outstanding adhesion for a wide range of substrates. EverSeal bonds aggressively to PVC, aged TPO, metal, steel, aluminum, ceramics, spray foam, Styrofoam, EPS, glass, wood, fiberglass, concrete, bituminous and modified bituminous materials, silicone, and coated metals. Contact your local sales representative for specific applications. Always perform a pull test to ensure proper adhesion.

| Property | Result |
|---|---|
| **Tensile Strength:** | **200 psi** |
| **Elongation at break:** | **500%** |
| **Hardness Shore A** | **25 (5-day ambient cure)** |
| **Slump** | **Zero Slump** |
| **Application Temperature** | **13 to 200 Degrees F.** |
| **Low Temp Flex** | **-20° F** |
| **Service Temp** | **-40°F to 200°F** |
| **Shelf Life (when stored @ 40°F to 80°F)** | **12 months** |

### COLOR

White

### APPLICATION

Can be applied to most surfaces without primer.

### PACKAGING/SHIPPING INFORMATION

CONTAINER SIZE

10.3 and 28 fl. oz.
2 Gallon pail (7.6 liters)

SHIPPING CLASS

Class 55
Class 55

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Topps Products, Inc.,to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Topps Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TOPPS PRODUCTS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.