RustArrestor™

COLOR:

Clear

BASIC USES:

- Labor saving preparation for rust
- Neutralizes rust and eliminates need for sandblasting
- Loosens grime for easier cleaning
- Improves coating effectiveness

PRODUCT DESCRIPTION:

A package of two powerful cleaners simultaneously neutralize and dissolve surface rust as it stabilizes oxidation for coating with Topps Seal® water-free coatings. Applies by pump-up sprayer or rag mop at approximately 300 square feet per gallon, followed by power wash after just 10 minutes. May be repeated if needed for heavy rust. In cases of heavier rust, allow to sit up to 30 minutes prior to power washing.

FEATURES:

- Easy to use
- Clear
- Leaves no film

WET MATERIAL

Typical Product Characteristics:

Viscosity	Water
Weight per gallon	10 – 11.5 lb.
Flashpoint of solvent	>200° F.
VOC	<150 g/l
pH	0 - 2
Dry to touch @ 77° F (50% rel. humidity)	~ 15 min
Service Temperature	32° - 120° F

OMTDRA171627

Topps Products Inc. • P O Box 515, Stilwell, KS 66085-0515 USA
Tel. (913) 685-2500 • Fax. (913) 851-9700 • e-mail: support@toppsproducts.com