

Clear & Dry™ WB

Resin Based Penetrating Concrete, Masonry & Stone Wall and Floor Sealer INTERIOR/EXTERIOR

COLOR: Clear

- BASIC USES:**
- Damp-proofs uncoated exterior walls
 - Prevents efflorescence
 - Stops dusting and makes for easier pavement clean-up
 - Protect against surface damage caused by freezing moisture
 - Aids in preventing staining
 - For both Exterior and Interior use

PRODUCT DESCRIPTION: This all-weather resin based concrete and masonry sealer penetrates deep within porous, untreated concrete and masonry. It lines capillary channels and invisibly repels moisture, yet allows the building to breathe. The low odor, strong repellency polymer resins always make application a 1-coat treatment with excellent durability and use for both exterior and interior needs.

- FEATURES:**
- Transparent
 - Penetrating - works beneath the surface
 - Repels moisture instantly upon drying
 - Breathing
 - Won't flake, peel, or wash off once dried
 - Always a 1-Coat labor saving application

WET MATERIAL	Viscosity	Water thin
<i>Typical Product Characteristics:</i>	Weight per gallon	8.3 - 8.6 lb.
	Active Ingredient	12% min.
	pH	9.0 - 9.5
	VOC	0
	Dry to touch @ 77° F (50% rel. humidity)	< 2 hrs
	Service Temperature	-40° - 140° F

PRODUCT INSTALLATION

Product: #1200 Clear & Dry™ WB

PACKAGING

5 gallon U.S. pail
55 gallon barrel

DRY TIME (Air dry @77°F/50% Rel. Humidity)

Moisture resistance <4 hrs
Dry time is greatly affected by temperature, humidity, and airflow.

COVERAGE

One gallon per 150 ft²

SURFACE PREPARATION

Surface must be totally clean, dry, and free of any finishes or sealers. Make any needed mortar or joint repairs prior to sealing.

APPLICATION

Do a test in an inconspicuous area and allow to dry. Color changes to the surface are uncommon and typically minor, but should be checked for acceptability. Start at the top of the wall and apply by low pressure pump-up garden type sprayer, electric sprayer at low pressure, brush or paint roller with slight overlaps. Always work downward so that there are no drips or runs. Apply evenly and avoid streaking, being careful not to over-apply or apply to already dry material. Minor initial overlap shading will go away. Do not attempt to apply more than one coat. Interior applications, such as to floors, are best left overnight to dry before resuming normal traffic. Avoid application to glass, rubber, paint or other surfaces where the cured coating may be objectionable.

NOTE

Product must not be allowed to freeze. Apply only when temperatures are 55° F and rising. Application is stable to light precipitation outdoors in as little as 2 hrs at 70° or warmer on breezy days.

CLEAN-UP

Use soapy water when wet.